★寄茶



仅限货机 CAO





中国认可 检验 INSPECTION CNAS IB0071 货物运输条件鉴定书

Certification for Safe Transport of Chemical Goods

危险品

样品名称:

可充电锂电池电池组 Li 18650 24V 6.6Ah 158.4Wh

Sample name:

Lithium-ion Battery Li 18650 24V 6.6Ah 158.4Wh

委托单位:

永康飞客电子科技有限公司

Yongkang Fotec Electronic Technology Co., LTD.

生产单位:

永康飞客电子科技有限公司

YongKang Fotec Electronic Technology Co., LTD



上海化工院检测有阻公司

Shanghai Research Institute of Chemical Industry Testing Co., Ltd

★ 空 运 By Air

★ 空 运 By Air

货物运输条件鉴定书

NO. 2119378066 Page 1/3

Certification for Safe Transport of Chemical Goods

			Certification for Safe Transport of	of Chemical Good	IS		
样品名		中文					
Sam		英文 English					
委托单位 Consignor			永康飞客电子科技有限公司 Yongkang Fotec Electronic Technology Co., LTD.				
生产单位			永康飞客电子科技有限公司 YongKang Fotec Electronic Technology Co., LTD				
Manufacturer 检验方法、程序 Inspection method and procedure			国际航空运输协会《危险品规则》60版 IATA Dangerous Goods Regulations (DGR) 60th Edition				
样品外观 Sample appearance			黑色塑胶外壳 Black Plastics cement shell				
包装件信息 Package information			/				
序号 NO.	电池种类 Battery type		型号 Model		Capacity 量Li content	Placement	
1	可充电锂离子电池组 Rechargeable Li-ion battery Li 18650 6. 6Ah 158. 4Wh Battery only					电池单独运输 Battery only	
鉴	I DEN	1.危险性识别(Hazards identification) Application Applicatio					
定结	TI ON CONCL	UN Number:UN3480 3. 包装要求 (Packaging requirements) 按包装说明965第IA部分要求办理。 The goods are packaged according to the Packaging Instruction 965 section IA. (Q限货机。 Cargo Aircraft Only. 检验日期: Inspection Date: 2019-01-22					
论	USI ON						
备注 Comment		/		4 卷	登台がま用音	短24	

批准 Approver:

杨小树

审核 Checker:

我之地

主检 Appraiser: 品情





货物运输条件鉴定书

Certification for Safe Transport of Chemical Goods

序号	检验结果及其他事项					
No.	Inspection results and other things					
1	本报告所述锂电池按照《危险品规则》(60版)[以下简称DGR]3.9.2.6.1(e)规定的质量管理体系进行制造。本报告所述锂电池不属于因安全原因召回的锂电池。本报告所述锂电池不进行以回收或处置为目的的航空运输,不属于废弃锂电池。本报告所述锂电池不进行以回收或处置为目的的航空运输,不属于废弃锂电池。Lithium cells and batteries listed in this report were manufactured under the quality management programme as described in IATA DGR 60th 3.9.2.6.1(e). Lithium cells and batteries listed in this report are not the defective cells or batteries returned to the manufacturer for safety reasons. Lithium cells and batteries listed in this report are not waste lithium cells or batteries, and they will not be shipped for recycling or disposal.					
2	本报告所述锂电池已通过《联合国试验和标准手册》第III部分38.3小节相应测试要求。 Lithium cells and batteries listed in this report are of the types proven to meet the requirements of each applicable test in the UN Manual of Tests and Criteria, Part III, sub-section 38.3.					
3	锂电池必须完全封装在内包装内,位于坚固的外包装中。完成包装件必须满足II级包装的性能要求。 Lithium cells and batteries must be packed in inner packagings that completely enclose the cell or battery and lithium cells are packaging. The completed package must meet the Packing Group II performance requirements.					
4	电池具有适当的防短路措施。 Cells and batteries are properly protected to prevent short circuits.					
5	每个包装件必须使用9类锂电池危险性标签(DGR图7.3.X)。 每个包装件必须贴有"仅限货机"标签(DGR图7.4.B)。 Each package must be labelled with the Class 9-Lithium Battery hazard label(Figure 7.3.X in IATA DGR). Each package must be labelled with the "Cargo Aircraft Only" label(Figure 7.4.B in IATA DGR).					
6	根据委托单位声明,本报告所述锂离子电池交付运输时,其荷电状态必须不超过额定容量的30%。 According to the statement of the consignor, lithium ion cells and batteries listed in this report must be offered for transport at a state of charge (SoC) not exceeding 30% of their rated capacity.					
7	电池不得与第1类爆炸品(1.4S项除外), 2.1项易燃气体, 第3类易燃液体, 4.1项易燃固体或5.1项氧化性物质等危险品包装在同一外包装内。 Cells and batteries must not be packed in the same outer packaging with dangerous goods classified in Class 1 (explosives) other than Division 1.4S, Division 2.1 (flammable gases), Class 3 (flammable liquids), Division 4.1 (flammable solids) or Division 5.1 (oxidizers).					
	-验证码:236235-					







货物运输条件鉴定书


Certification for Safe Transport of Chemical Goods











永康飞客电子科技有限公司 Yongkang Fotec Electronic Technology Co., LTD

型号Model til 18650 24V 6.5Ah 15B.《新 研究服用Standard voltage 24V 标称等Mosinal capacity 5.6Ah 下作用Poperatina voltage:18.9-29.4V 出电电影Max charge current:3A 安全电影Max discharge current:18A 十二年(1816)

UN38. 3 MSDS (E







